

1. Identification

Product identifier	ELECTROLYTE SOLUTION	
Other means of identification		
Product code	1282	
Recommended use	professional, scientific and technical activities: other professional, scientific and technical activities	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	GFS Chemicals, Inc.	
Address	P.O. Box 245 Powell, OH 43065 United States	
Telephone	Phone	740-881-5501
	Toll Free	800-858-9682
	Fax	740-881-5989
Website	www.gfschemicals.com	
E-mail	service@gfschemicals.com	
Emergency phone number	Emergency Assistance	Chemtrec 800-424-9300

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Serious eye damage/eye irritation	Category 2A
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 1 (central nervous system, kidney, systemic toxicity)
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2 (blood vessel, liver, spleen)
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Highly flammable liquid and vapor. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. Causes damage to organs (central nervous system, kidney, systemic toxicity). May cause damage to organs (blood vessel, liver, spleen) through prolonged or repeated exposure.
Precautionary statement	
Prevention	Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe the mist or vapor. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician if you feel unwell. If eye irritation persists: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention.

Storage	Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ISOPROPYL ALCOHOL	ISOPROPANOL 2-PROPANOL	67-63-0	96.6
WATER		7732-18-5	3.1
SODIUM ACETATE, TRIHYDRATE		6131-90-4	0.3

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Do not use mouth-to-mouth method if victim ingested the substance. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Behavioral changes. Decrease in motor functions. Edema. Narcosis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Jaundice. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Carbon dioxide (CO ₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Should not be released into the environment. Prevent entry into waterways, sewers, basements or confined areas.

Large Spills: Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Clean contaminated surface thoroughly. Prevent entry into waterways, sewer, basements or confined areas. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.

Small Spills: After removal flush contaminated area thoroughly with water. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Never return spills in original containers for re-use.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
ISOPROPYL ALCOHOL (CAS 67-63-0)	PEL	980 mg/m ³
		400 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
ISOPROPYL ALCOHOL (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

US. NIOSH: Pocket Guide to Chemical Hazards Components

Components	Type	Value
ISOPROPYL ALCOHOL (CAS 67-63-0)	STEL	1225 mg/m ³
	TWA	500 ppm
		980 mg/m ³
		400 ppm

Biological limit values**US. ACGIH. BEIs. Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
ISOPROPYL ALCOHOL (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Clear.
Physical state	Liquid.
Form	Liquid.
Color	Colorless.
Odor	Alcoholic.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-127.3 °F (-88.5 °C) estimated
Initial boiling point and boiling range	180.5 °F (82.5 °C) estimated
Flash point	53.6 °F (12.0 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	2.5 % estimated
Flammability limit - upper (%)	12 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.

Vapor pressure	60.53 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	750.2 °F (399 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.794 g/cm3 estimated
Flammability class	Flammable IB estimated
Flash point class	Flammable IC
Percent volatile	99.7 % estimated
Specific gravity	0.79 estimated
VOC (Weight %)	97 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable at normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Isocyanates. Chlorine.
Hazardous decomposition products	May include oxides of carbon.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs by inhalation. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Behavioral changes. Decrease in motor functions. Edema. Narcosis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Jaundice. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation.

Information on toxicological effects

Acute toxicity Narcotic effects. May cause respiratory irritation.

Product	Species	Test Results
ELECTROLYTE SOLUTION (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	10810 mg/kg
<i>Oral</i>		
LD50	Dog	5383 mg/kg
	Mouse	4040 mg/kg
	Rabbit	8086 mg/kg
		5.207 g/kg estimated
	Rat	5777 mg/kg
		4.8654 g/kg estimated

Product	Species	Test Results
<i>Other</i>		
LD50	Mouse	1693 mg/kg
	Rat	1137.6812 mg/kg estimated
Components	Species	Test Results
ISOPROPYL ALCOHOL (CAS 67-63-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	5030 - 7900 mg/kg 12800 mg/kg
<i>Oral</i>		
LD50	Dog	4797 mg/kg
	Mouse	3600 mg/kg 4.5 g/kg
	Rabbit	8000 mg/kg 6410 mg/kg 5.03 g/kg
	Rat	4700 - 5800 mg/kg 5045 mg/kg 4.7 g/kg
<i>Other</i>		
LD50	Mouse	1509 mg/kg
	Rat	1099 mg/kg
SODIUM ACETATE, TRIHYDRATE (CAS 6131-90-4)		
Acute		
<i>Oral</i>		
LD50	Mouse	4960 mg/kg
	Rat	3530 mg/kg 3500 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
Reproductive toxicity	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity - single exposure	Causes damage to organs (central nervous system, kidney, systemic toxicity). May cause respiratory irritation. May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	May cause damage to organs (blood vessel, liver, spleen) through prolonged or repeated exposure.
Aspiration hazard	Not available.
Chronic effects	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
--------------------	--

Product	Species		Test Results
ELECTROLYTE SOLUTION (CAS Mixture)			
Aquatic			
Crustacea	LC50	Daphnia	11222 mg/l, 24 Hours 1599 mg/l, 48 Hours 1347 mg/l, 96 Hours
Fish	LC50	Fish	13276 mg/l, 1 Hours 7612 mg/l, 48 Hours 7175 mg/l, 96 Hours 6857 mg/l, 24 Hours 5211 mg/l, 72 Hours

Components	Species		Test Results
ISOPROPYL ALCOHOL (CAS 67-63-0)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

ISOPROPYL ALCOHOL 0.05

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number UN1219
UN proper shipping name Isopropanol or Isopropyl alcohol
Transport hazard class(es)
Class 3
Subsidiary risk -
Label(s) 3
Packing group II
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Special provisions IB2, T4, TP1
Packaging exceptions 4b, 150
Packaging non bulk 202
Packaging bulk 242

IATA

UN number UN1219
UN proper shipping name Isopropanol
Transport hazard class(es)
Class 3
Subsidiary risk -

Packing group	II
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1219
UN proper shipping name	ISOPROPANOL (ISOPROPYL ALCOHOL)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes
	Delayed Hazard - Yes
	Fire Hazard - Yes
	Pressure Hazard - No
	Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312

No

Hazardous chemical**SARA 313 (TRI reporting)**

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. Massachusetts RTK - Substance List

ISOPROPYL ALCOHOL (CAS 67-63-0)

US. New Jersey Worker and Community Right-to-Know Act

ISOPROPYL ALCOHOL (CAS 67-63-0)

US. Pennsylvania Worker and Community Right-to-Know Law

ISOPROPYL ALCOHOL (CAS 67-63-0)

US. Rhode Island RTK

ISOPROPYL ALCOHOL (CAS 67-63-0)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision**Issue date** June-09-2015**Version #** 01

Disclaimer GFS Chemicals cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision Information Product and Company Identification: Alternate Trade Names
 Composition / Information on Ingredients: Ingredients
 Physical & Chemical Properties: Multiple Properties
 Transport Information: Proper Shipping Name/Packing Group