

1. Identification

Product identifier WATERMARK® KARL FISCHER COULOMETRIC GENERATOR SOLUTION, UNIVERSAL

Other means of identification

Product code 2321

Recommended use Laboratory reagent for water determination using the Karl Fischer method.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name GFS Chemicals, Inc.

Address P.O. Box 245
Powell, OH 43065
United States

Telephone Phone 740-881-5501
Toll Free 800-858-9682
Fax 740-881-5989

Website www.gfschemicals.com

E-mail service@gfschemicals.com

Emergency phone number Emergency Assistance Chemtrec 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Health hazards Acute toxicity, dermal Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2

Sensitization, skin Category 1

Carcinogenicity Category 2

Reproductive toxicity Category 1

Specific target organ toxicity, repeated exposure Category 1

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3

Hazardous to the aquatic environment, long-term hazard Category 3

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe the mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response	IF ON SKIN: Wash with plenty of soap and water. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Keep container tightly closed. Store in a well-ventilated place. Keep cool.
Disposal	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	1-3% of the mixture consists of component(s) of unknown acute oral toxicity. 10-20% of the mixture consists of component(s) of unknown acute dermal toxicity. 10-20% of the mixture consists of component(s) of unknown acute inhalation toxicity. 80-90% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 80-90% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ETHYLENEGLYCOLMONOMETHYL ETHER	METHYL CELLOSOLVE ETHYLENE GLYCOL MONOMETHYL ETHER 2-METHOXYETHANOL	109-86-4	80 - < 90*
DIETHANOLAMINE	BIS(2-HYDROXYETHYL)AMINE	111-42-2	10 - < 20*
IODINE		7553-56-2	1 - < 3*
SULFUR DIOXIDE		7446-09-5	1 - < 3*

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

Material name: WATERMARK® KARL FISCHER COULOMETRIC GENERATOR SOLUTION, UNIVERSAL

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe the mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
ETHYLENEGLYCOLMONOME THYL ETHER (CAS 109-86-4)	PEL	80 mg/m3
IODINE (CAS 7553-56-2)	Ceiling	25 ppm
		1 mg/m3
		0.1 ppm
SULFUR DIOXIDE (CAS 7446-09-5)	PEL	13 mg/m3
		5 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
DIETHANOLAMINE (CAS 111-42-2)	TWA	1 mg/m3	Inhalable fraction and vapor.
ETHYLENEGLYCOLMONOME THYL ETHER (CAS 109-86-4)	TWA	0.1 ppm	
SULFUR DIOXIDE (CAS 7446-09-5)	STEL	0.25 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards Components

Components	Type	Value
DIETHANOLAMINE (CAS 111-42-2)	TWA	15 mg/m3
ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4)	TWA	3 ppm
		0.3 mg/m3
IODINE (CAS 7553-56-2)	Ceiling	0.1 ppm
		1 mg/m3
SULFUR DIOXIDE (CAS 7446-09-5)	STEL	0.1 ppm
		13 mg/m3
		5 ppm
	TWA	5 mg/m3
		2 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4)	1 mg/g	2-Methoxyacetic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

DIETHANOLAMINE (CAS 111-42-2) Can be absorbed through the skin.

ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4) Skin designation applies.

US - Tennessee OELs: Skin designation

ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

DIETHANOLAMINE (CAS 111-42-2) Can be absorbed through the skin.

ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4) Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles). Eye wash fountains are required.

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor cartridge.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties**Appearance**

Clear.

Physical state

Liquid.

Form	Liquid.
Color	Light yellow.
Odor	Strong.
Odor threshold	Not available.
pH	6
Melting point/freezing point	-42 °F (-41 °C) estimated
Initial boiling point and boiling range	255 °F (124 °C) estimated
Flash point	115 - 140 °F (46 - 60 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	2.4 % estimated
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	374 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Miscible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	640 °F (338 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	1.10 g/cm ³
Explosive properties	Not explosive.
Flammability class	Combustible II estimated
Flash point class	Combustible II
Oxidizing properties	Not oxidizing.
Percent volatile	83.2 % estimated
Specific gravity	1.1
VOC	83.2 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Caustics.
Hazardous decomposition products	Upon decomposition, this product emits oxides of sulfur, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Harmful in contact with skin.

Product	Species	Test Results
WATERMARK® KARL FISCHER COULOMETRIC GENERATOR SOLUTION, UNIVERSAL		
Acute		
Inhalation		
LC50	Guinea pig	6278 mg/l
	Mouse	6389 mg/l
	Rat	2308 mg/l
Oral		
LD50	Mouse	99999 mg/kg
	Rabbit	99999 mg/kg
Components		
Species		
Test Results		
DIETHANOLAMINE (CAS 111-42-2)		
Acute		
Dermal		
LD50	Rabbit	11.9 ml/kg
Oral		
LD50	Rat	1820 mg/kg
		710 mg/kg
Other		
LD50	Mouse	2300 mg/kg
ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4)		
Acute		
Dermal		
LD50	Rabbit	1280 mg/kg
Inhalation		
LC50	Rat	1500 mg/l 7 hours
Oral		
LD50	Guinea pig	950 mg/kg
	Mouse	2560 mg/kg
	Rabbit	890 mg/kg
	Rat	2370 mg/kg
Other		
LD50	Mouse	2147 mg/kg
	Rat	2140 mg/kg
IODINE (CAS 7553-56-2)		
Acute		
Oral		
LD50	Mouse	22 g/kg
	Rabbit	10 g/kg
	Rat	14 g/kg
SULFUR DIOXIDE (CAS 7446-09-5)		
Acute		
Inhalation		
LC50	Guinea pig	1000 ppm, 20 Hours
		1000 mg/l, 20 Hours
		130 ppm, 154 Hours
		130 mg/l, 154 Hours

Components	Species	Test Results
	Mouse	1000 ppm, 4 Hours
		1000 mg/l, 4 Hours
		150 ppm, 847 Hours
		150 mg/l, 847 Hours

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
DIETHANOLAMINE (CAS 111-42-2)	2B Possibly carcinogenic to humans.	
SULFUR DIOXIDE (CAS 7446-09-5)	3 Not classifiable as to carcinogenicity to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not regulated.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Not listed.		
Reproductive toxicity	May damage fertility or the unborn child.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	

12. Ecological information

Ecotoxicity	Harmful to aquatic life with long lasting effects.		
Product	Species		
Test Results			
WATERMARK® KARL FISCHER COULOMETRIC GENERATOR SOLUTION, UNIVERSAL			
Aquatic			
Crustacea	EC50	Daphnia	468.1818 mg/l, 48 hours estimated
	LC50	Daphnia	15385 mg/l, 24 hours
			140 mg/l, 48 hours
			38.25 mg/l, 96 hours
Fish	LC50	Fish	15385 mg/l, 48 hours
			147 mg/l, 24 hours
			107 mg/l, 96 hours
Components	Species		
Test Results			
DIETHANOLAMINE (CAS 111-42-2)			
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	61.8 - 86.04 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	100 mg/l, 96 hours
ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	> 10000 mg/l, 96 hours

Components	Species	Test Results
IODINE (CAS 7553-56-2)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)
		0.48 - 0.58 mg/l, 96 hours
		0.48 - 0.58 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

DIETHANOLAMINE	-1.43
ETHYLENEGLYCOLMONOMETHYL ETHER	-0.77
IODINE	2.49

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1188
UN proper shipping name	Ethylene glycol monomethyl ether mixture
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Special precautions for user	Not available.
Special provisions	B1, IB3, T2, TP1
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242

IATA

UN number	UN1188
UN proper shipping name	Ethylene glycol monomethyl ether mixture
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Not available.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number UN1188
UN proper shipping name ETHYLENE GLYCOL MONOMETHYL ETHER MIXTURE
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group III
Environmental hazards
Marine pollutant No.
EmS F-E, S-D
Special precautions for user Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT**IATA; IMDG****15. Regulatory information**

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

DIETHANOLAMINE (CAS 111-42-2) Listed.

SARA 304 Emergency release notification

SULFUR DIOXIDE (CAS 7446-09-5) 500 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
 Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
SULFUR DIOXIDE	7446-09-5	500	500		

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
DIETHANOLAMINE	111-42-2	10 - < 20
ETHYLENEGLYCOLMONOMETHYL ETHER	109-86-4	80 - < 90

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

DIETHANOLAMINE (CAS 111-42-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

SULFUR DIOXIDE (CAS 7446-09-5)

Safe Drinking Water Act (SDWA) Not regulated.**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

IODINE (CAS 7553-56-2) 2.2 %WV

DEA Exempt Chemical Mixtures Code Number

IODINE (CAS 7553-56-2) 6699

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

SULFUR DIOXIDE (CAS 7446-09-5) High priority

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

DIETHANOLAMINE (CAS 111-42-2) Listed: June 22, 2012

US - California Proposition 65 - CRT: Listed date/Developmental toxin

ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4) Listed: January 1, 1989

SULFUR DIOXIDE (CAS 7446-09-5) Listed: July 29, 2011

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4) Listed: January 1, 1989

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))DIETHANOLAMINE (CAS 111-42-2)
ETHYLENEGLYCOLMONOMETHYL ETHER (CAS 109-86-4)
SULFUR DIOXIDE (CAS 7446-09-5)**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Toxic Chemical Substances (TCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	February-14-2013
Revision date	December-22-2016
Version #	02

Disclaimer

The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. GFS Chemicals, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.